


Version 3 31/12/2002	 <b>Safety Data Sheet</b> <b>Distitron 100 BSX15</b>
-------------------------	---

---

## 1: Chemical Product and Company Identification

---

### Distitron 100 BSX15

**Producer** : Lonza SpA  
Via del Pruneto 40  
I-52027 San Giovanni Valdarno (AR)  
ITALY  
Telefono: ++39 055 91281

**Agent** : Lonza SpA  
Via Enrico Fermi 51  
I-24020 Scanzorosciate BG  
Telefono: ++39 035 652 111

**Emergency telephone number** : Via del Pruneto 40 I-52027 San Giovanni Valdarno  
++39 055 9128503/91281

---

## 2: Composition/Information on Ingredients

---


**Unsaturated polyester** : > 50 %

**Styrene** : Concentration 12,5 - 43 %  
: EINECS/ELINCS 202-851-5  
: CAS 100-42-5

**Classification 67/548/CEE** :  
Index N° 601-026-00-0  
Harmful; Xn;  
R:10-20-36/38

**Alfa-methylstyrene**  
: < 2,5 %  
: EINECS/ELINCS 202-705-0  
: CAS 98-83-9

**Classification 67/548/CEE** :  
Index N° 601-027-00-6  
Xi; N;  
R:10-36/37-51/53

Version 3	
31/12/2002	<div style="text-align: center;">             Safety Data Sheet            Distitron 100 BSX15         </div>

---

### 3: Hazards Identification

Flammable.

Harmful by inhalation.

Irritating to eyes and skin.

---

### 4: First Aid Measures

Inhalation	: Remove from area to fresh air. Seek medical attention if respiratory irritation develops or if breathing becomes difficult.
Skin contact	: After contact with skin, wash immediately with plenty of soap and water. Seek medical attention if irritation develops and persists.
Eye contact	: For eye contact, flush eyes with running water for at least 15 minutes. Hold eyelids apart to ensure rinsing of the entire surface of the surface of the eyes and lids with water. Get medical attention.
Ingestion	: If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Call a physician.

---

### 5: Fire-fighting Measures

Suitable extinguishing media	: dry powder, carbon dioxide (CO2), foam, water spray, Do not use solid water stream.
Specific hazards during fire fighting	: Hazardous gases produced in fire under conditions that produce incomplete combustion may consist of carbon monoxide and aromatic hydrocarbons
Special protective equipment for fire-fighters	: Use personal protective equipment.
Additional advice	: Water mist may be used to cool closed containers.

---

### 6: Accidental Release Measures

Personal precautions	: Use personal protective equipment. Keep people away from and upwind of spill/leak. Remove all sources of ignition.
Environmental precautions	: Keep spill out of sewers and open bodies of water. Do not wash remainder with water.

Version 3 31/12/2002	[REDACTED]
<b>Safety Data Sheet</b> <b>Distitron 100 BSX15</b>	

Methods for cleaning up : Absorb spill with inert material (sand, earth, ...) and give the liquid and solid in separate containers for recovery or disposal. Keep spill out of sewers and open bodies of water.

## 7: Handling and Storage

### Handling

Safe handling advice : Provide sufficient air exchange and/or exhaust in work rooms.

Advice on protection against fire and explosion : Danger! Flammable material. Keep away from heat and sources of ignition. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Incompatible with oxidizing agents.

### Storage

Requirements for storage areas and containers : Keep in a dry, cool and well-ventilated place. To maintain product quality, do not store in heat or direct sunlight.

Other data : Keep container tightly closed.

### Storage stability

Stable at normal conditions

## 8: Exposure Controls/Personal Protection

### Components with workplace control parameters

Styrene (CAS-No.: 100-42-5)

ACGIH-TLV

Exposure limit(s) : 20 ml/m<sup>3</sup> 85 mg/m<sup>3</sup>  
Short term exposure limit : 40 ml/m<sup>3</sup> 170 mg/m<sup>3</sup>

DFG-MAK/BAT/TRK (2000)

Exposure limit(s) : 20 ppm 86 mg/m<sup>3</sup>

SUVA-MAK(2001)

Exposure limit(s) : 20 ppm 85 mg/m<sup>3</sup>

Value IDLH : 700 ppm

**Alfa-Methylstyrene** ( No. CAS: 98-83-9 )

Version 3  
31/12/2002

Safety Data Sheet  
Distitron 100 BSX15

ACGIH-TLV

Exposure limit(s) : 50 ppm 242 mg/m3  
Short term exposure limit : 100 ppm 483 mg/m3

**Personal protective equipment**

Hygiene measures : Avoid contact with skin, eyes and clothing. Do not breathe vapor. Wash hands before breaks and immediately after handling the product.

Respiratory protection : Mask with A-type filter for organic vapours.

Hand protection : solvent-resistant gloves

Eye protection : safety glasses

---

**9: Physical and Chemical Properties**

---

**Appearance**

State of aggregation : liquid (25.0°C)  
Colour : blue  
Odour : styrene-like

**Safety relevant data**

Boiling point/range : 145.0°C (760.00 mmHg) (ref. Styrene)  
Density : 1.07 - 1.15 g/cm3 (25.0°C)  
Relative vapour density : 3.600 (ref. Styrene)  
Vapour pressure : 7.0 mbar (20°C)( ref. Styrene)  
Water solubility : 0.30 g/l insoluble  
pH : Not applicable  
Viscosity, dynamic : Tixotropic  
Flash point : closed cup : 31°C  
Method: ISO 3680  
Upper explosion limit : 8.0 %(V) (ref. Styrene)  
Lower explosion limit : 1.1 %(V) (ref. Styrene)

Version 3 31/12/2002	[REDACTED]
<b>Safety Data Sheet</b> <b>Distitron 100 BSX15</b>	

Ignition temperature : 490°C (ref. Styrene)

**10: Stability and Reactivity**

Hazardous reactions : When heated at relatively high temperature, the resin polymerizes spontaneously. This reaction could be strongly exothermic.

Decomposition products : Carbon oxides, Aromatic hydrocarbons.

Conditions to avoid : Heat.

Materials to avoid : strong oxidizing agents.

**11: Toxicological Information**

The following toxicological data refer to:

Styrene (CAS-No.: 100-42-5)

Acute oral toxicity (LD50) : 2650 mg/kg Species: rat

Acute inhalation toxicity (LC50) : 12 mg/l Species: rat  
Exposure time: 4 h

Skin irritation : mild irritant Species: rabbit

**Alfa-Methylstyrene** (No. CAS: 98-83-9)

Acute oral toxicity (LD50) : 4900 mg/kg Species: rat

**12: Ecological and Ecotoxicological Information**

Additional advice : At present time is no ecotoxicological information available.


**13: Disposal Considerations**

Waste from residues : Dispose of in compliance with all federal, state and local laws and regulations.

**14: Transport Information**

( # )

ADR : Class: 3

Version 3 31/12/2002	
Safety Data Sheet Distitron 100 BSX15	

Packaging group: III  
Label: Flammable Liquid No. 3  
HI No. : 30

RID : Class: 3  
Packaging group: III  
Label: Flammable Liquid No. 3  
HI No. : 30

ICAO/ATA : Class: 3 Packaging group: III  
Label: Flammable Liquid No. 3  
Packing instruction (cargo aircraft): 310  
Packing instruction (passenger aircraft): Y 309

IMDG-Code: : Class: 3.3  
Packaging group: III  
Label: Flammable Liquid No. 3  
EmS: 3-05

UN/ID No. : 1866  
Proper shipping name : Resin solution, flammable

---

### 15: Regulatory Information

---

Hazardous material : yes  
Additional advice : Classification and labelling according to Directive 1999/45/CE

EU Index No. : The product is a mixture

Symbols/indications of danger :



Harmful

R-phrases) R10: Flammable.  
R20: Harmful by inhalation.  
R36/38: Irritating to eyes and skin.

S-phrases) S23: Do not breathe vapour.


---

### 16: Other Information

---

Other instructions/regulations : The product is a preparation. The components are listed in TSCA and EINECS.

( # ) on the left indicate the modifications with respect to the last version.

Version 3	
31/12/2002	Safety Data Sheet Distitron 100 BSX15

---

The information contained herein is believed to be correct and corresponds to the latest state of scientific and technical knowledge. However, no warranty is made, either express or implied, regarding its accuracy or the results to be obtained from the use of such information.